

Friction Lock Type

<p>F - Type female plug (AWG 22 to 28)</p> <p>Order Code housing: CRF-1xx-F254</p>	<p>F - Type -THT- male</p> <p>Order Code straight: CRS-1xx-F254-99 right angle: CRR-1xx-F254-99</p>
--	---

Female Header Type

<p>H - Type female dual row - without bump (AWG 22 to 28)</p> <p>Order Code housing: CRF-2xx-H254</p>	<p>H - Type female dual row - with low bump (AWG 22 to 28)</p> <p>Order Code housing: CRF-2xx-H254/P</p>	<p>H - Type female dual row - with high bump (AWG 22 to 28)</p> <p>Order Code housing: CRF-2xx-H254/HP</p>
<p>H - Type female single row - without bump (AWG 22 to 28)</p> <p>Order Code housing: CRF-1xx-H254</p>	<p>H - Type female contact</p> <p>if for single row 01-19 & dual row 04-18 contacts: Order Code: CRF-999L-H254-95</p> <p>if for single row 20-40 & dual row 20-80 contacts: Order Code: CRF-999-H254-95</p>	

SPECIFICATIONS

Current rating	3 A	Operating temp.	-25°C to +90°C
Insulator resistance	1000 MΩ min.	Contact material	Copper alloy
Contact resistance	20 mΩ max.	Insulator material	Nylon UL 94 V-2
Withstanding voltage	1000 V AC	F-Type	P.B.T. UL 94 V-0
Voltage rating	250 V AC max.	H-Type	
		PCB Thickness	1.60 mm (.063")

H - Type male contact

Order Code: **CRM-999-H254-55**

How to order

CR X - x xx - X 254 - 99

<p>Type</p> <p>Header Type: R = R/A male S = Straight male</p> <p>Contact Type: F = Female M = Male</p>	<p>Rows</p> <p>1 = single row 2 = double row 9 = loose contacts</p>	<p>Nbr of contacts</p> <p>02 - 20 = F - type 01 - 40 = H - type - 1 row 04 - 80 = H - type - 2 row 99 = loose contact MOQ: 10K / reel</p>	<p>Execution</p> <p>F = F - type H = H - type</p> <p>Refer to above drawings for details</p>	<p>Plating</p> <p>99 = tin 55 = gold</p> <p>NOTE: for CRF-999-H254 & CRF-999L-H254 only tin/gold plating available</p> <p>Code: 95</p>
--	---	--	--	---