



REV.	DESCRIPTION	DATE	DRAWN
A	New	16.12.2016	Cherry
B	General update	03.07.2019	Cheng




Order Code
M08-MA03-CVFP-55/00

Specifications

Electrical
 Current rating: 3A per contact
 Insulation resistance: 100MΩ min.
 Voltage rating: 60V AC/DC
 Withstanding voltage: 1000V AC

Mechanical Requirements
 Waterproof rate: IP68
 Recommended panel thickness: 0.80 to 4.00mm
 Recommended Torque: 9~10 kgf-cm
 Operating life: 100 cycles min.

In accordance with IEC 61076-2-104:2014




Recommended Panel Cut-out



Item	Part Name	Materials / Finish(Color)	Q'TY
1	Housing	Thermoplastic / Black	1
2	Metal Body	Copper Alloy / Ni Plated	1
3	Hex Nut	Copper Alloy / Ni Plated	1
4	O-Ring	NBR / Black	1
5	Contact	Copper Alloy / Au Plated	3
6	Glue	Epoxy / Black	-

E-tec 2019 © - all rights reserved www.e-tec.asia



UNIT	mm	GENERAL TOLERANCE		DRAWN	Cherry	DATE	16.12.2016	DWG. NO.	M08-MA03-CVFP-55/00	SHEET	1/1
SCALE	Free	X.° ±	X. ±	CHECK	Cheng	DATE	03.07.2019	SERIES NO.	M08-MA03-CVFP-55/00	REV.	B
		.XX° ±	.XX ± 0.20	APPROVE	Fagi	DATE	03.07.2019				
		.XXX° ±	.XXX ±								

M8 Circular Connector
3-Pin Male A - Coding Type
 Solder Cup - Panel Front Mount