


# Mini – Flex Connector

IDC pitch 1.27mm shrouded male



### Specifications

Current rating	1.0 A max.
Voltage rating	230 V AC/DC
Withstanding voltage	500 V AC
Contact resistance	20 mΩ max.
Insulation resistance	1000 MΩ min.
Operating temperature	- 40°C to +105°C
Insulator material	(RoHS compliant) PBT (red) UL 94 V-0
Contact material	(RoHS compliant) Phosphor Bronze

### Ribbon Cable Recommendation

Cable Type	Ribbon UL Style 2651
Spacing	1.27mm
Wire range	stranded 0.08 – 0.09 mm <sup>2</sup> AWG 28 solid Ø 0.30 mm
Insulation Diameter	0.90 mm

### Dimensions (mm)

Contacts	DIM "A"	DIM "B"	Contacts	DIM "A"	DIM "B"	Contacts	DIM "A"	DIM "B"
004	8.45	3.81	012	18.61	13.97	020	28.77	24.13
006	10.99	6.35	014	21.15	16.51	022	31.31	25.40
008	13.53	8.89	016	23.69	19.05	024	33.85	27.94
010	16.07	11.43	018	26.23	21.59	026	36.39	30.48

### How to order

MFM - xxx - DC50 - 99

Nbr of contacts
004; 006; 008; 010 012; 014; 016; 018 020; 022; 024; 026

Plating
99 = Tin (leadfree) other platings on request