

S - Type Single Row

<p>Female Plug</p> <p>Order Code Housing: CRF-1xx-S125 Contact: CRF-999/35-S125-99</p>	<p>-THT- Male Header straight (top entry) & right angle (side entry)</p> <p>Order Code straight: CRS-1xx-S125-99/S right angle: CRR-1xx-S125-99</p>
<p>-SMT- Male Header right angle (side entry)</p> <p>Order Code: CRR-1xx-SS125-99/R</p>	<p>-SMT- Male Header straight (top entry)</p> <p>Order Code: CRS-1xx-SS125-99/R CRS-1xx-SS125-99/B</p>

D - Type Single Row

<p>Female Plug</p> <p>Order Code Housing: CRF-1xx-D125 Contact: CRF-999/35-D125-95</p>	<p>-SMT- Male Header right angle (side entry)</p> <p>Order Code: CRR-1xx-SD125-99/R</p>
--	---

Specifications

Current rating	1 A	Withstanding voltage	250 V AC	Contact material	Copper Alloy
Insulation resistance	100 MΩ min.	Operating temperature	-40°C to +85°C	Insulator material	PA6T UL 94V-0
Contact resistance	20 mΩ max.	D125 Type	-25°C to +85°C	CRF Type	PA66 UL 94V-0
Voltage rating	125 V AC	SMT Processing temp.	+250°C for 5 sec.	SD125 Type	PA9T UL 94V-0
				PCB thickness	1.60 mm

How to order

CR X - x xx - X 125 - 99 / X

Type	Rows	Nbr of Contacts	Execution	Plating	Packing
F = Female R = R/A Male S = Straight Male	1 = single row <i>if Crimp Contact:</i> 9	02 - 15 = S & SS - Type 02 - 30 = D & SD - Type <i>if Crimp Contact: (MOQ: 10K/reel)</i> 99/35 = AWG 28~32	S = Plug SS = SMT D = Plug SD = SMT for details see above dwg's	99 = Tin 95 = Tin/Gold (tin leadfree) other platings on request	R = Reel w/o PickUp Cap B = Reel with PickUp Cap