


**PCB Hole Layout**



**Specifications**

Current rating	2 A
Insulation resistance	1000 MΩ min.
Withstanding voltage	500 V AC
Operating temperature	- 40°C to +105°C
Contact material	Copper alloy <i>(RoHS compliant)</i>
Insulator material	PBT or PA6T, UL 94 V-0 <i>(RoHS compliant)</i> <b>Standard : PBT</b>

Pin code	DIM "A"	DIM "B"	DIM "C"
<b>143/02</b>	6.80 mm	2.80 mm	4.70 mm
<b>104/01</b>	2.70 mm	2.70 mm	5.00 mm
<b>136/02</b>	5.30 mm	3.20 mm	5.10 mm
<b>191/01</b>	9.30 mm	4.30 mm	5.50 mm
<b>117/01</b>	2.80 mm	2.80 mm	6.10 mm
<b>143/01</b>	4.00 mm	2.80 mm	7.50 mm
<b>143/03</b>	2.40 mm	3.90 mm	8.00 mm
<b>150/01</b>	4.00 mm	2.50 mm	8.50 mm
<b>163/01</b>	4.00 mm	2.80 mm	9.50 mm
<b>180/03</b>	5.00 mm	3.00 mm	10.00 mm
<b>170/01</b>	3.00 mm	3.00 mm	11.00 mm
<b>180/02</b>	3.00 mm	3.00 mm	12.00 mm
<b>210/01</b>	6.00 mm	3.00 mm	12.00 mm
<b>260/04</b>	9.00 mm	4.00 mm	13.00 mm
<b>220/01</b>	4.00 mm	2.80 mm	15.25 mm
<b>252/02</b>	5.20 mm	4.20 mm	15.80 mm
<b>300/03</b>	10.00 mm	3.00 mm	17.00 mm
<b>225/01</b>	2.50 mm	2.50 mm	17.50 mm
<b>270/02</b>	4.00 mm	3.00 mm	20.00 mm
<b>410/01</b>	9.00 mm	4.00 mm	28.00 mm
<b>432/01</b>	3.20 mm	3.20 mm	36.80 mm

other dimensions on request

**How to order**

**SP x - xxx - X xxx/xx - 55/2**

